

## SAFETY DATA SHEET (SDS)

### 1: Identification

**PRODUCT IDENTIFICATION:** SolarGuard<sup>®</sup> Reflective Insulation

**COMPANY:** Silvercote, LLC  
979 Batesville Rd. Suite B  
Greer, SC 29651

**CONTACT:** Environmental Health & Safety Manager  
844-232-3701

**24-HOUR EMERGENCY  
RESPONSE INFORMATION:** Chemtrec 1-800-424-9300

### 2: Hazard Identification



**WARNING**

Eye, skin and respiratory tract irritant.

**Hazard Statement**

Inhalation: Fiberglass wool may cause mechanical irritation of the upper respiratory tract.  
Direct contact with the skin may cause mechanical irritation.

### 3: Composition/Information On Ingredients

<u>COMPONENT</u>	<u>CAS#</u>
Fiber Glass Wool	65997-17-3
Acrylic thermoset resin	N/A
Urea extended phenol-melamine formaldehyde resin (cured)	25212-25-3
Urea extended phenol-formaldehyde resin (cured)	25104-55-6

### 4: First Aid Measures

**Skin Contact:** Do not rub. Wash with soap and water. Use skin cream to sooth irritation. Wash clothes separately. A shower after work is recommended. Irritation typically will not persist if good personal hygiene habits are followed.

**Eye Contact:** Flush with running water for at least 15 minutes. Using sterile eye wash, flush foreign bodies from eyes.

**Inhalation:** Remove from exposure. If irritation persists in any of these situations, a physician should be consulted.

### 5: Fire-Fighting Measures

**Flash Point:** N/A

**Flammability Limits:** N/A

**Auto-Ignition Temperance:** N/A

**Extinguishing Media:** Water, foam, dry chemical

**Special Fire-fighting Procedure:** None

**Unusual Fire Hazards:** Fiberglass insulation is a non-flammable product. The packaging material will burn, and caution should be used when working close to the facing or packaged material with open flame. Chemicals in plastic packaging products that do not present a health hazard under normal conditions may be released during a fire. Toxic fumes and gases that may result from incomplete combustion include carbon monoxide, hydrogen chloride and low-level cyanides. In case of overexposure, remove to fresh air. If breathing is difficult, administer oxygen and consult a physician.

### 6: Accidental Release Measures

**Cleanup:** Avoid dust-generating means of clean-up.

### 7: Handling And Storage

Store faced or packaged material away from sources of ignition and have fire-fighting equipment available.

## 8: Exposure Controls/Personal Protection

**Exposure Limits:** Inhalation. Fiberglass wool may cause mechanical irritation of the upper respiratory tract. Use of a 2-strap NIOSH-Approved N-95 Filtering Facepiece respirator, such as a 3M model 8210 or equivalent is recommended when handling loose-fill, when exposure is unknown or when fibers exceed the TLV of 1 f/cc. Operations which generate high airborne fiber concentrations (over 10 times the TLV) require additional respiratory protection.

**Skin Contact:** Direct contact with the skin may cause mechanical irritation. If irritation occurs, long sleeves, loose fitting clothing, gloves, and eye protection are recommended. Wash exposed areas with soap and water after handling. Wash clothes separately and rinse out washer after each use.

Following a thorough review of all the medical data available, the International Agency for Research on Cancer (IARC) has classified glass wool insulation as Group #3, "not classifiable as to carcinogenicity to humans". IARC has stated there is "no evidence of increased risks of lung cancer or of mesothelioma... from occupational exposures during the manufacture of these materials, and inadequate evidence overall of any cancer risk.

### COMPONENT

Fiber Glass Wool

Acrylic thermoset resin

Urea extended phenol-melamine formaldehyde resin (cured)

Urea extended phenol-formaldehyde resin (cured)

### EXPOSURE LIMITS

OSHA PEL: 15 mg/M<sup>3</sup> (total dust)

5 mg/M<sup>3</sup> (respirable dust)

N/A

N/A

N/A

## 9: Physical And Chemical Properties

**Boiling Point (\*f):** N/A

**Vapor Pressure (mm Hg.):** N/A

**Vapor Density (Air=1):** N/A

**Solubility in Water:** None

**Specific Gravity (H<sub>2</sub>O) = 1:** 2.6

**Percent Volatile By Volume:** <1%

**Evaporation Rate:** N/A

## 10: Stability And Reactivity

**Stability:** Stable

**Incompatibility:** None

**Hazardous Polymerization:** Will not occur

## 11: Toxicological Information

Data not available

## 12: Ecological Information

This material is not regulated under hazardous waste regulations.

## 13: Disposal Considerations

Dispose of scrap material according to federal, state and local regulations.

## 14: Transport Information

Reference Bill of Lading

## 15: Regulatory Information

N/A

## 16: Other Information

The information provided in this SDS is accurate to the best of Silvercote, LLC's knowledge and is provided in good faith. No warranty is given with respect to its accuracy and/or reliability. The information relates only to the particular product and not to the product when used in combination with any other materials. It is the user's responsibility to take proper precautions when using this product and ensure its own compliance with applicable local, state and federal laws and regulations.

Revised August 2014

**Please contact your Silvercote Sales Representative  
for more information at (844) 232-3701 or [info@silvercote.com](mailto:info@silvercote.com)**