



SKY-WEB II®

FALL PROTECTION AND INSULATION SUPPORT SYSTEM

Sky-Web II fall protection and insulation support system is an exceptional, economical mesh system that offers passive fall protection during construction and performs as an insulation support system after the job is completed.

Increases Safety and Efficiency

The 2 3/4" diamond nylon mesh can be installed with no difficulty at all. Once structural members are in place, Sky-Web II offers leading edge fall protection so that workers can move about freely without the inconvenience and lost productivity associated with tie-off systems. Fall protection will still be required for work at the perimeter of the roof.

Reduces Injury

When using a traditional tie-off system, a jolt may be suffered when the lanyard stops a worker's fall. With the Sky-Web II system, the worker will only fall a short distance before being caught by the mesh. The Sky-Web II system cannot protect against injuries from falls onto structural members. In addition, tie-off systems are still required for workers near the perimeter of the building and during the mesh installation process.

Easy Installation

Sky-Web II is a made-to-order product that arrives at the job site with all of the instructions and required hardware necessary to complete the installation. The system can accommodate every building configuration, with the exception of skews, hips and valleys. Its attachment is made around the perimeter of the building with v-straps attached to the secondary roof members with specially designed self-tapping screws.

Individual mesh pieces can be made in one piece to any building width and up to 60' in bay length, thus eliminating the need to make numerous field splices. Once construction is complete, the mesh remains as a permanent part of the roof system, providing support for the insulation materials. The product's white color blends well with most fiberglass insulation facings, maintaining an attractive and nearly invisible appearance.

General

- The Fall Protection and Insulation Support System is the Sky-Web II system as furnished by Silvercote and installed in accordance with the manufacturer's instructions.
- The system is compatible with most pre-engineered metal roof systems.
- The system must be installed over the top of the roof's secondary structural members with adequate structural attachment in accordance with the manufacturer's installation instructions.

Specifications

- Mesh: knotted mesh on a nominal 2-3/4" by 2-3/4" grid. The mesh is made from twisted twine of DuPont™ nylon Type 6-6 fiber. The mesh covering interior bays is made from #21 twine. The mesh covering end bays is made from #21 twine except a 6' strip along the edge which is made from #30 twine. This edge is color coded for identification.
- The mesh has a double selvage along the two edges in the machine direction.
- The mesh is furnished in single pieces in any building width up to 60' in length. This means that a building that is 200' wide with 30' bays will have pieces furnished that are 200' by 60' in size. The pieces will normally be ordered so that splices can be made over frame lines.
- The #21 twine and the #30 twine used to make the mesh have a minimum tensile strength of 205 pounds and 265 pounds, respectively. The #21 twine has a runnage of 960 feet per pound and the #30 twine has a runnage of 605 feet per pound.
- The cord used to make the mesh-to-mesh edge connections is a #36 DuPont™ nylon Type 6-6 white braided twine. It has a minimum tensile strength of 350 pounds and a runnage of 533 feet per pound.
- The mesh weight is 0.012 pounds per square foot.

Application

- The roof structural system must be in place prior to installation.
- The Sky-Web II system remains in place after the metal roofing is installed.
- The system must be fastened to structural framing at the perimeter of the building. Mesh-to-mesh connections must be made above the interior frames.
- The installed system should conform to the geometry of the fiberglass blanket insulation in order to maintain the roof system's designed insulation value.

Fasteners and Hardware

Connections to the eave members and to the gable members are made with 1/8" diameter wire clips looped through 20 gauge steel v-straps in accordance with the manufacturer's instructions. The steel v-straps are fastened to the framing with self-drilling screws in accordance with the manufacturer's installation instructions.

Fire Hazard Classification

The Sky-Web II system has a Flame Spread Index of 3 or less and a Smoke Developed Index of less than 10 as tested in accordance with U.L. 723.

OSHA Information

The U.S. Department of Labor, Occupational Safety and Health Administration (OSHA) does not provide approvals or endorsements of products or methods. However, OSHA does evaluate concepts to ascertain their likelihood of providing compliance with applicable safety standards. OSHA reviewed the Sky-Web II system and concluded that, when properly installed; it would "...provide adequate interior fall protection and be in compliance with OSHA's fall protection standards." The Sky-Web II system does not, however, eliminate the fall hazard from the perimeter of the roof. OSHA document 29 CFR 1926 (u) (3), requires that workers be protected from falls along all roof edges to which they are exposed. Quality assurance testing, witnessed by an independent consulting firm, provided verification of the system's capabilities.

**Please contact your Silvercote Sales Representative
for more information at (844) 232-3701 or info@silvercote.com**