

CONDENSATION BLANKET

Description

Condensation Blanket is composed of a lightweight, versatile and easy-to-install insulation roll.

Condensation Blanket is available in standard 4' and 6' widths to provide ease in handling, storage and installation. Contact your sales representative for further details.

Uses

Condensation Blanket is ideally suited for condensation protection in semi-conditioned pre-engineered metal buildings and post-frame structures.

Benefits

- Helps protect the building's metal skin and structure from rust due to condensation.
- Improves the interior appearance and light reflectance.
- Reduces wind noise problems which occur with typical uninsulated metal roofs.

Technical Data

*Fire Hazard Classification: (Composite test of fiberglass adhesive and facing)	Flame Spread <25 Smoke Developed <50
Corrosion Resistance:	Will not accelerate corrosion of steel or copper.
Resistance To Fungi And Bacteria:	Does not breed or promote fungi or bacteria growth.

*The ASTM E84 standard is used solely to measure and describe properties of materials and products in response to heat and flame under controlled laboratory conditions. This numerical flame spread is not intended to reflect hazards presented by this or any other material under actual fire conditions. Results are reported to the nearest five rating.

NOTE: Condensation Blanket is NOT sold as a thermal barrier. The insulating value of the product is negligible and should NOT be utilized in applications where thermal performance is required.

Compliance and Specification Data

ASTM C665

ASTM E84, FHC - 25/50*

**PLEASE CONTACT YOUR SILVERCOTE SALES REPRESENTATIVE
FOR MORE INFORMATION AT (844) 232-3701 OR INFO@SILVERCOTE.COM**