



AG™ STABLE R

Description

As part of the ThermaCare Stable airtight Envelope Solutions, Ag™ Stable R is a long term proprietary and patented stabilized agricultural attic insulation with a consistent thermal performance. A white virgin fiberglass with bio-based binder providing no shifting and no settling.

Application

Attic blown stabilized insulation for agriculture, installed in open attics of new and existing houses.

Packaging

Nominal bag weight: 32 lbs.

Ordering units

Packs/pallet: 39 bags

MOQ: Pallet



Performance properties

Thermal value: ASTM C518

Standard specification for mineral fiber loose-fill thermal insulation: Type 1 ASTM C764

Open Attic Application

| R-Value To obtain an insulation resistance (R) of: | Bags Per 1000 Ft ² No. of bags per 1,000 ft ² shall not be less than: | Maximum Coverage Contents of bag shall not cover more than: (ft ²) | Minimum Weight Weight per square foot shall not be less than: (lbs/ft ²) | Installed Thickness Installed insulation shall not be less than: (in) | Minimum Settled Thickness Installed insulation shall not be less than: (in) |
|--|---|---|--|--|--|
| 13 | 9.4 | 106.3 | 0.301 | 5.38 | 5.38 |
| 19 | 13.6 | 73.7 | 0.434 | 7.75 | 7.75 |
| 20 | 14.4 | 69.3 | 0.462 | 8.25 | 8.25 |
| 21 | 15.1 | 66.3 | 0.483 | 8.63 | 8.63 |
| 22 | 15.8 | 63.5 | 0.504 | 9.00 | 9.00 |
| 23 | 16.6 | 60.2 | 0.532 | 9.50 | 9.50 |
| 24 | 17.3 | 57.9 | 0.553 | 9.88 | 9.88 |
| 25 | 17.9 | 55.7 | 0.574 | 10.25 | 10.25 |
| 26 | 18.6 | 53.8 | 0.595 | 10.63 | 10.63 |
| 27 | 19.5 | 51.4 | 0.623 | 11.13 | 11.13 |
| 28 | 20.1 | 49.7 | 0.644 | 11.50 | 11.50 |
| 29 | 20.8 | 48.1 | 0.665 | 11.88 | 11.88 |
| 30 | 21.4 | 46.6 | 0.686 | 12.25 | 12.25 |
| 34 | 24.5 | 40.8 | 0.784 | 14.00 | 14.00 |
| 38 | 27.3 | 36.6 | 0.875 | 14.75 | 14.75 |

FOR MORE INFORMATION (864) 603-2836 · AG.INFO@SILVERCOTE.COM