#### SILVERCOTE.COM



#### TECHNICAL DATA SHEET

# AG<sup>™</sup> 3M TAPE

# Description

As part of the ThermaCare Stable airtight Envelope Solution, Ag<sup>™</sup> 3M Tape is a unique composite copolymer film laminated to a bi-directional woven copolymer alloy for extremely high tensile strength. The self-crosslinking acrylic adhesive, creates a strong, permanent bond. Humidity and temperature resistant with and excellent performance at high and low temperatures. Available in black and white.

# Application

Bi-directional woven copolymer patch tape for seaming and patching.

### **Dimensions**

Width: 4" Length: 55 YD

## **Ordering unit**

Pack: 15 Packs/pallet: 36

#### **Performance Properties**

Product Thickness	7.0 mil (0.18 mm) excluding liner PSTC 133
Peel Adhesion	30 oz/in (8.3 N/25 mm) (-20 min. dwell) PSTC 131
Shear Adhesion	>24 hrs @ 2.2 psi (>24 hrs @ 15.2 kPa) PSTC 131
Tensile Strength	55 lb/in (248.6 N/25 mm) PSTC 131
Elongation	30% PSTC 131



# FOR MORE INFORMATION (864) 603-2836 · AG.INFO@SILVERCOTE.COM